

# Halfen Curtain wall edge-of-slab anchoring questionnaire

In order for us to be able to select the most efficient anchoring systems for your project, please:

1. Select appropriate 'Halfen adjustable curtain wall clips' or provide dimensions "A" through "Q" for custom clips (by others), as applicable.
2. Fill project information, questions 1-10 below.
3. Fax to 210-658-7908 or email to [halfen@meadowburke.com](mailto:halfen@meadowburke.com)

DEAD LOAD		WIND LOAD																							
<input type="checkbox"/> HCWL1 HCWR1		<table border="1"> <tr><td>A</td><td>4.25"</td></tr> <tr><td>B</td><td>2.75"</td></tr> <tr><td>C</td><td>4.50"</td></tr> <tr><td>D</td><td>.375"</td></tr> <tr><td>E</td><td>2.25"</td></tr> <tr><td>F</td><td>2.50"</td></tr> <tr><td>G</td><td>1.00"</td></tr> <tr><td>H</td><td>2.00"</td></tr> <tr><td>J</td><td>1.406"</td></tr> <tr><td>L</td><td>1.5625"</td></tr> <tr><td>M</td><td>2.25"</td></tr> </table>	A	4.25"	B	2.75"	C	4.50"	D	.375"	E	2.25"	F	2.50"	G	1.00"	H	2.00"	J	1.406"	L	1.5625"	M	2.25"	<input type="checkbox"/> HWLC1
A	4.25"																								
B	2.75"																								
C	4.50"																								
D	.375"																								
E	2.25"																								
F	2.50"																								
G	1.00"																								
H	2.00"																								
J	1.406"																								
L	1.5625"																								
M	2.25"																								
<input type="checkbox"/> HCWL2 HCWR2		<table border="1"> <tr><td>A</td><td>5.25"</td></tr> <tr><td>B</td><td>2.75"</td></tr> <tr><td>C</td><td>5.00"</td></tr> <tr><td>D</td><td>.375"</td></tr> <tr><td>E</td><td>2.50"</td></tr> <tr><td>F</td><td>2.50"</td></tr> <tr><td>G</td><td>2.00"</td></tr> <tr><td>H</td><td>2.00"</td></tr> <tr><td>J</td><td>1.406"</td></tr> <tr><td>L</td><td>1.5625"</td></tr> <tr><td>M</td><td>3.25"</td></tr> </table>	A	5.25"	B	2.75"	C	5.00"	D	.375"	E	2.50"	F	2.50"	G	2.00"	H	2.00"	J	1.406"	L	1.5625"	M	3.25"	<input type="checkbox"/> HWLC2
A	5.25"																								
B	2.75"																								
C	5.00"																								
D	.375"																								
E	2.50"																								
F	2.50"																								
G	2.00"																								
H	2.00"																								
J	1.406"																								
L	1.5625"																								
M	3.25"																								
<input type="checkbox"/> HCWL3 HCWR3		<table border="1"> <tr><td>A</td><td>6.25"</td></tr> <tr><td>B</td><td>2.75"</td></tr> <tr><td>C</td><td>5.50"</td></tr> <tr><td>D</td><td>.375"</td></tr> <tr><td>E</td><td>2.75"</td></tr> <tr><td>F</td><td>2.50"</td></tr> <tr><td>G</td><td>3.00"</td></tr> <tr><td>H</td><td>2.00"</td></tr> <tr><td>J</td><td>1.406"</td></tr> <tr><td>L</td><td>1.5625"</td></tr> <tr><td>M</td><td>4.25"</td></tr> </table>	A	6.25"	B	2.75"	C	5.50"	D	.375"	E	2.75"	F	2.50"	G	3.00"	H	2.00"	J	1.406"	L	1.5625"	M	4.25"	<input type="checkbox"/> HWLC3
A	6.25"																								
B	2.75"																								
C	5.50"																								
D	.375"																								
E	2.75"																								
F	2.50"																								
G	3.00"																								
H	2.00"																								
J	1.406"																								
L	1.5625"																								
M	4.25"																								

A: \_\_\_\_\_  
 B: \_\_\_\_\_  
 B': \_\_\_\_\_  
 C: \_\_\_\_\_  
 D: \_\_\_\_\_  
 E: \_\_\_\_\_  
 F: \_\_\_\_\_  
 G: \_\_\_\_\_  
 H: \_\_\_\_\_  
 J: \_\_\_\_\_  
 K: \_\_\_\_\_  
 L: \_\_\_\_\_  
 M: \_\_\_\_\_  
 N: \_\_\_\_\_  
 P: \_\_\_\_\_  
 Q: \_\_\_\_\_

Project Name: \_\_\_\_\_ Location: \_\_\_\_\_

Concrete Strength  $f'c$ : \_\_\_\_\_ psi.  Normal weight concrete  Light wt. concrete

Dead load "DL" \_\_\_\_\_ lbs. Wind load "WL" \_\_\_\_\_ lbs.

If "DL" and "WL" are not known, please provide the following:

Floor-to-floor height: \_\_\_\_\_ ft. Mullion centers: \_\_\_\_\_ ft.

Curtain wall system weight: \_\_\_\_\_ psf. Wind pressure: \_\_\_\_\_ psf. Wind suction: \_\_\_\_\_ psf.

## MEADOW-BURKE PRODUCTS

8521 F.M. Road 1976 P.O. Box 547 Converse, TX 78109  
 Phone: 800-323-6896 or 210-658-4671 FAX: 888-277-1695 or 210-658-7908